

SUPERCUBE II®

LOOSE-FILL FIBERGLASS INSULATION



- Non-Corrosive
- Non-Flammable
- Non-Combustible
- Pest-Resistant

Coverage Information

To achieve the stated R-values, the insulation must be installed at the minimum thickness and maximum coverages. Failure to install both the required bags and at least the minimum thickness will result in lower insulation R-value. Net coverage includes framing.

Not for exposed applications. Insulation should not be installed over eave vents or near light fixtures or other heat generation devices.

SUPERCUBE II® COVERAGE INFORMATION				
R-VALUE	BAGS PER 1000 SQ FT	MAXIMUM NET COVERAGE	MINIMUM WEIGHT PER SQ. FT.	MINIMUM THICKNESS
R-60	33.3	30 SF	1.155 LBS.	21.75"
R-49	26.3	38 SF	0.925 LBS.	18.25"
R-44	23.2	43 SF	0.822 LBS.	16.75"
R-38	20.0	50 SF	0.701 LBS.	14.75"
R-30	15.4	65 SF	0.541 LBS.	12.00"
R-26	13.3	75 SF	0.462 LBS.	10.75"
R-22	11.6	86 SF	0.385 LBS.	9.25"
R-19	10.0	100 SF	0.327 LBS.	8.25"
R-13	6.7	150 SF	0.212 LBS.	6.00"
R-11	5.8	172 SF	0.173 LBS.	5.25"

BAG WEIGHT: 35 LBS., MINIMUM: 33 LBS. FOR PNEUMATIC APPLICATION ONLY.

Specifications

This product meets or exceeds the requirements of C 764, Type 1.

Thickness values determined in accordance with ASTM C 1374.

Flame Spread 5, Smoke Developed 5.

Thermal Resistance values determined in accordance with, ASTM C 687, C 518.

Material passes the requirements of ASTM E 136 Combustion Characteristics.

GREENGUARD® Environmental Institute.



Indoor air quality is a growing concern with today's tighter construction practices for homes and buildings, and the importance of using healthy, low emitting

products and materials is a major component in maintaining safer, healthy indoor environments.

The GREENGUARD Certification Program™ was founded to establish a true third party certification based on proven emissions criteria used by the State of Washington,

the U.S. Environmental Protection Agency, OSHA and the World Health Organization to implement an indoor air quality (IAQ) management plan that addresses all factors potentially impacting IAQ. These include emissions from construction materials, indoor furnishings, and processes such as cleaning and operation of office equipment.

Supercube II® loose-fill insulation is tested and certified to meet the tough GREENGUARD® IAQ standards. This gives you the confidence that by using Supercube II® you are assured of excellent IAQ performance.